


NUMERIC MESSAGING

ONE WAY PAGER NP88+

Great Things Come From Small Packages



Narrow Band Available

Unication Numeric Pager

The NP88⁺ offers accessibility to stay on top of your busy lifestyle. Perfect for basic wireless communication and user-frendly operation. You can set the pager to generate an audible or a vibration alert no matter under noisy or quiet environments when you are expecting an import page. The NP-88⁺ is compact, lightweight, inexpensive, and the best choice when you need reliable paging with broad coverage.

NUMERIC PAGER

Model Type

NP88⁺ Numeric Pager POCSAG
Synthesized





FEATURE LIST:

DISPLAY:

- Backlight
 In low-light conditions, the backlight makes the screen easy to read.
- * Standby Screen
 The standby screen displays the time of day / date or no display.
- * Time of Day and Day/Month
 The time of day the date are displayed whether the pager is on or off.
- * Direct Show Message
 If Enable this function, When pager received message, the pager direct show message for user preview.

LNDICATORS/ALERT:

- * Low Battery Indicator
 When battery power reaches low levels, low
 cell is displayed, prompting you to change the
 battery. All pagers alert change to two seconds
 in length.
- * Automatic Alert Reset

 The pager alerts automatically stop, even if no buttons are pressed.
- * Personal Alarm

 This alarm can be set to alert you. The alarm works even when the pager is off.
- * User Selectable of five alert tones give you a choive of message alerts heard when you are paged in the audible alert mode D.

MESSAGING:

- * Duplicate Messages
- If the same message is received more than once, duplicate sign is displayed at the beginning of the latest message. This message contains the latest timestamp and prevents a repeated message from taking an extra memory slot.
- Messages Erase
 Messages can be erased all at once or
 selectively at your choice to free space in
 memory.
- * Memory Retention
 All messages remain in memory, even when the pager is off and while the battery is being replaced.
- * Memory Capacity
 The NP88+ POCSAG pager can store up to sixteen
 20-character messages, for a total of 320
 characters.
- * Message Protect
 You can protect up to eight messages stored in the pager memory.
- * Overflow
- Overflow is displayed when more unread messages are received than the available message memory can hold. After you read all of your unread messages, the standby screen is displayed.
- * Timestamp
 The time and the date of a message received are displayed on the screen after each message.

For more information, please contact.

NP88+ / NP88 W POCSAG

Product Specifications:

Band splits	VHF	UHF	900 MHz	
Frequency Range	137~143 MHz			
	143~153 MHz	450~460 MHz	929~932 MHz	
	153~163 MHz	460~470 MHz		
	163~174 MHz			
Baud Rate (bps)	512, 1200, 2400 bps			
Code Format	POCSAG (CIR NO.1 NRZ FSK)			
Address Capability	6 Capcodes			
Paging Sensitivity	512 bps : \leq 5 u/Vm	512 bps : ≦ 6 u/Vm	512 bps : ≦ 6 u/Vm	
(u/Vm)Best Position	1200 bps : \leq 7 u/Vm	1200 bps : \leq 8 u/Vm	1200 bps : ≦ 8 u/Vm	
Maximum	2400 bps : \leq 10 u/Vm	2400 bps : ≦ 10 u/Vm	2400 bps : ≦ 10 u/Vm	
Selectivity	≧60 dB	≧55 dB	≥50 dB	
Frequency Stability	≦± 15 ppm	≦± 5 ppm	≦± 3.5 ppm	
Spurious & Image Rejection	≥50 dB		≧40 dB	
Channel Spacing	12.5 KHz / 25 KHz		25 KHz	
Receiver Type	Synthesized			
Frequency Deviation	± 4.5 KHz			
Alert Tone SPL	≥78 dB@ 12 in (2730)Hz Standard Alert)			
Operating Temperature	5°C to 40°C (40°F to 105°F)			
Storage Temperature	-40°C to +85°C			
Power Supply	1.5V Single AAA –Size Alkaline Battery			
Battery Life (Estimated		512 Baud = 25 days		
battery life is based on	1200 Baud = 23 days			
full battery capacity	2400 Baud = 20 days			
and 2 pages/day)	2400 baud = 20 days			
Low Battery Alert Level	1.2 Voits			
Weight with Battery	60g			
Dimensions (LxWxH/mm)	63.65 x 45.0 x 17.5 mm (2.5 x 1.77 x 0.69 in)			

